

## SPL 3000c1



### Specifications:

<i>Channels</i>	<i>no</i>	<b>1</b>
<i>Class</i>	<i>Typ</i>	<b>D</b>
<i>Power @14,4V /3.0% THD</i>		
<i>@ 4 ohm:</i>	<i>Wrms</i>	<b>1000</b>
<i>@ 2 ohm:</i>	<i>Wrms</i>	<b>1850</b>
<i>@ 1 ohm:</i>	<i>Wrms</i>	<b>3100</b>
<i>Operation supply</i>	<i>V</i>	<b>10 -16</b>
<i>Thermal protection</i>	<i>°C</i>	<b>80</b>
<i>THD @ 4 Ω / 50% Pmax</i>	<i>%</i>	<b>0,1</b>
<i>Signal/noise</i>	<i>dB</i>	<b>71</b>
<i>Efficiency (4 ohm)</i>	<i>%</i>	<b>88</b>
<i>Input sensitivity</i>	<i>Vrms</i>	<b>0,2-6</b>
<i>Low input impedance</i>	<i>Ω</i>	<b>20 k</b>
<i>Damping @ 80 Hz</i>		<b>187</b>
<i>Power consumption, idle</i>	<i>A</i>	<b>3</b>
<i>Power cons. 4 Ω</i>	<i>A</i>	<b>78</b>
<i>Power cons. 2 Ω</i>	<i>A</i>	<b>156</b>
<i>Weight</i>	<i>kg</i>	<b>7,42</b>
<i>Dimensions</i>	<i>l/w/h</i>	<b>524/235/52 mm</b>

### Features:

- *Lowpass filter with 24 dB dB slope.*
- *Subsonic filter*
- *Phase shift 0 - 180°*
- *Bass adjust 0 – 12 dB*
- *Optional remote available*

### Miscellaneous:

- *Protection for overhead, over current, short circuitry and speaker DC protection*
- *Massive heavy aluminum-heat sink*