

XL 150c4



Specifications:

Channels	no	4
Class	Typ	AB Full Mosfet
Power @14,4V /1.0% THD		
@ 4 ohm stereo:	Wrms	4x 146
@ 2 ohm stereo:	Wrms	4x 225
@ 4 ohm mono:	Wrms	2x 450
Operation supply	V	10 -16
Thermal protection	C	80
THD @ 4 Ω / 50% Pmax	%	0,03
Signal/noise	dB	91
Band width +- 1 dB	Hz	16-41000
Input sensitivity	Vrms	0,2-8
Low input impedance	Ω	10 k
High input impedance	Ω	33
Damping @ 80 Hz		425
Power consumption, idle	A	1
Power cons. 4 Ω stereo	A	42
Power cons. 4 Ω mono	A	81
Power cons. 2 Ω mono	A	N.A.
Weight	kg	4,5
Dimensions	l/w/h	424/180/58 mm

Features:

- *Input with low- or high-level signal*
- *Input 2- or 4- channel mode*
- *High-level with autosense function (no remote signal required)*
- *Variable switchable Low Pass Filter from 50 to 300 Hz*
- *Variable switchable High Pass Filter from 25 to 175 Hz*
- *12 dB octave crossover slope*

Miscellaneous:

- Protection for overhead, over current, short circuitry and speaker DC protection
- Massive heavy aluminum-heat sink with intelligent fan cooling